

Kinetico® Powerline™ PRO Series Filters

Iron & Sulfur

Ensure the highest quality water for your home efficiently, effectively and effortlessly. No need for expensive regenerants.

- Two available tank sizes and three media blends with traditional top-mount or exclusive side-mount control valve options
- Protect water-using appliances, fixtures and clothing from iron staining
- Eliminate the rotten-egg odor caused by hydrogen sulfide gas in your water
- Fully programmable control valve with simple setup app for smartphones and tablets



Kinetico® Powerline™ PRO Series Filters

Iron & Sulfur

Product Highlights

State-Of-The-Art: Fully programmable, field-proven control valve can be set up using local handheld devices* such as smartphones and tablets, or by simply using two buttons on valve faceplate.

Customizable: Two available tank sizes deliver a strong flow of clean, filtered water throughout any size home, while a choice of three media blends provides maximum flexibility for dealers.

Unique: Industry-exclusive features include external air injectors, independently programmable air draw and backwash cycles, and Macrolite® RX filtration media.

Highly efficient: Valve utilizes a forward- and reverse-drive motor to maximize efficiency.

Cleaner operation: External air induction directly into the media tank reduces control valve fouling.

Protective valve cover: One-piece sliding cover minimizes weather and insect issues, while providing quick, no-tools access.

Corrosion-resistant media tanks: Long-lasting media vessels can endure harsh environments.

Superior backwash capability: Vortech distributor plate provides exceptional media “lift” and backwashing effectiveness.

Low voltage with power backup: Operates on 12-volt DC power with a simple 9-volt battery backup.

**See Owner's Manual for more details.*



Kinetico®
POWERLINE™ PRO



Kinetico®
POWERLINE™ PRO_{SV}



Available Tank Sizes

- 10 x 54 PRO, Vortech distributor; for top-mount valve
- 13 x 54 PRO, Vortech distributor; for top-mount valve
- 10 x 54 PRO SV, standard distributor; for side-mount valve
- 13 x 54 PRO SV, standard distributor; for side-mount valve

Available Media Options

- Iron Filter blend with Macrolite RX
- Sulfur Filter blend with Macrolite RX
- Oxidizer Feed blend with Macrolite RX
 - All blends sold pre-measured in 5 gallon buckets
 - 10 x 54 systems require two buckets of media
 - 13 x 54 systems require three buckets of media

Legacy View App

- Conveniently view and change all valve settings using smartphone or tablet
- Easily check valve status and current water usage*
- Start system regeneration/backwash from tablet or phone
- View system history graphs of water usage, flow rates and other key information*
- Enter servicing water treatment dealer contact information

**Requires optional flow meter*



Kinetico® Powerline™ PRO Series Filters

Iron & Sulfur

Powerline PRO Filter Specifications

Specification	PF 1054 PRO - Iron	PF 1054 PRO - Sulfur	PF 1354 PRO - Iron	PF 1354 PRO - Sulfur
Valve	Standard	Standard	Standard	Standard
Tank	10x54	10x54	13x54	13x54
Lower Distributor	Vortech	Vortech	Vortech	Vortech
Media	Iron Blend	Sulfur Blend	Iron Blend	Sulfur Blend
Amount	2 Buckets - 1.42 cf	2 Buckets - 1.42 cf	3 Buckets - 2.13 cf	3 Buckets - 2.13 cf
Gravel	No	No	No	No
pH	6.8 - 9	5 - 9	6.8 - 9	5 - 9
Service Flow	5 gpm	4 gpm	7 gpm	6 gpm
Peak Flow	8 gpm	8 gpm	10 gpm	10 gpm
Maximum Iron	7 ppm	2 ppm	7 ppm	2 ppm
Maximum H ₂ S	0.5 ppm	6 ppm	0.5 ppm	6 ppm
Maximum Manganese	0.5 ppm	0.2 ppm	1 ppm	0.2 ppm
Backwash Time	12 min	12 min	12 min	12 min
Backwash Flow	5 gpm	3.5 gpm	7 gpm	6 gpm
Air Draw Time	45 min	45 min	45 min	45 min
DF Rinse Time	5 min	5 min	5 min	5 min
Air Activ. Timing	300 - 500 gallons	300 - 500 gallons	300 - 500 gallons	300 - 500 gallons
Backwash Timing	3 Days Minimum	3 Days Minimum	3 Days Minimum	3 Days Minimum

Powerline PRO SV Filter Specifications

Specification	PF 1054 PRO SV Iron	PF 1054 PRO SV Sulfur	PF 1054 PRO SV Oxidizer	PF 1354 PRO SV Iron	PF 1354 PRO SV Sulfur	PF 1354 PRO SV Oxidizer
Valve	Pro	Pro	Pro	Pro	Pro	Pro
Tank	10x54	10x54	10x54	13x54	13x54	13x54
Lower Distributor	Conical	Conical	Conical	Conical	Conical	Conical
Media	Iron Blend	Sulfur Blend	Oxidizer Blend	Iron Blend	Sulfur Blend	Oxidizer Blend
Amount	2 Buckets - 1.42 cf	2 Buckets - 1.42 cf	2 Buckets - 1.42 cf	3 Buckets - 2.13 cf	3 Buckets - 2.13 cf	3 Buckets - 2.13 cf
Gravel	20 lbs.	20 lbs.	20 lbs.	50 lbs.	50 lbs.	50 lbs.
pH	6.8 - 9	5 - 9	5.8 to 10.5	6.8 - 9	5 - 9	5.8 to 10.5
Service Flow	5 gpm	4 gpm	6 gpm	7 gpm	6 gpm	8 gpm
Peak Flow	8 gpm	8 gpm	8 gpm	10 gpm	10 gpm	10 gpm
Maximum Iron	7 ppm	2 ppm	10-15 ppm	7 ppm	2.0 ppm	10-15 ppm
Maximum H ₂ S	0.5 ppm	6 ppm	8-12 ppm	0.5 ppm	6 ppm	8-12 ppm
Maximum Manganese	0.75 ppm	0.5 ppm	2 ppm	0.75 ppm	0.5 ppm	2 ppm
Backwash Time	12 min	12 min	12 min	12 min	12 min	12 min
Backwash Flow	5 gpm	5 gpm	5 gpm	7 gpm	7 gpm	7 gpm
Air Draw Time	45 min	45 min	45 min	45 min	45 min	45 min
DF Rinse Time	5 min	5 min	5 min	5 min	5 min	5 min
Air Activ. Timing	300 - 500 gallons	300 - 500 gallons	300 - 500 gallons	300 - 500 gallons	300 - 500 gallons	300 - 500 gallons
Backwash Timing	3 Days Minimum	3 Days Minimum	3 Days Minimum	3 Days Minimum	3 Days Minimum	3 Days Minimum